BILL OF QUANTITIES (BOQ) -C

BILL OF QUANTITIES (BOQ) -C MAHINDRA WORLD CITY, JAIPUR									
Road Maintenance Works in SEZ Zone at Mahindra World City Jaipur									
Sr. No.	Description	Unit	Qty	Rate (Rs.)	Amount (Rs.)				
1	Excavation, preparation and consolidation of sub-grade for road and utility corridor including surveying wherever necessary in any kind of soil, soft and hard murum with boulders and soft rock, up to required depth with hydraulic excavator of 0.9 cum bucket capacity including cutting and loading in tippers & unloading, trimming bottom and side slopes, in accordance with requirements of lines, grades and cross sections, and transporting to the location shown by the Engineer in charge watering, compacting, and consolidating the surface using by vibratory roller 8 to 10 T capacity to achieve 97% of maximum laboratory dry density (IS:2720 Part-8) with optimum moisture content etc and transporting the surplus excavated earth for filling or disposal within the project boundary all complete as specified and as per the direction of engineer-in-charge. (Payment shall be made for the finished item of work after compaction based on original and finished levels). Disposal of Soil upto lead of 1 km including levelling etc. as per direction of Engineer-in-Charge.	cum	0.00						
2	Preparation and consolidation of granular sub-base by providing close graded Material conforming to Table 400-1, Grading I of MoRT&H & H (Fifth Revision) specifications, in layers of maximum 150 mm. compacted thickness over compacted sub grade, to achieve a minimum soaked CBR value of 30% in accordance with standard specifications, including watering, mixing in a mechanical mix plant at OMC, carriage of mixed material by tippers to work site, for all leads & lifts, spreading in uniform layers of specified thickness with motor grader on prepared surface and compacting by 8-10 M.T. vibratory power roller to achieve the desired standard proctor density of 98% (IS:2720 Part - 8) including surveying wherever necessary etc. complete as per Clause 401 of MoRT&H specification and as per the direction of engineer-in-charge. (Payment to be made for finished item of work after completion based on original and finished levels) (175mm Thick)	cum	0.00						
3	Providing, laying, spreading and compacting graded stone aggregate of size 75 micron- 53mm from approved quarry to Wet Mix Macadam (WMM) of 2 layers (125 mm compacted thickness of each layers laying of WMM by pavers) specification with water to OMC in mechanical mix, carriage of mixed material by tipper to site, laying in uniform layers in base course on a well prepared under base and compacting with power vibratory roller to achieve the desired density including surveying wherever necessary etc complete as per Ref. clause No 406 of MORT&H - (Fifth Revision) and as per the direction of engineer-in-charge (125 mm thick)	cum	125.00						
4	Providing and applying prime coat over top surface of WMM, a single layer of low viscosity liquid bituminous material of medium curing cutback quality of SS (Slow setting emulsion) @ 0.7 kg. /sqm. (Ref. Clause No.502 of MORT&H-Fifth Revision) includes cost of bitumen emulsion, cleaning the surface by mechanical means and temporary covering on the Kerb to prevent bitumen spillage before applying the prime coat.	sqm	2000.00						
5	Providing and applying single tack coat of liquid bituminous material of RS (Rapid setting emulsion) on existing W.M.M surface which is preparatory to another bituminous construction over it as a tack coat @ 0.25 kg / sqm. Area, as per Table No.500-5 of MoRT&H (Fifth Revision) specifications. Including cost of bitumen emulsion, cleaning the surface by mechanical means and temporary covering on the Kerb to prevent bitumen spillage before applying the prime coat.	sqm	2000.00						
6	Providing and laying evenly graded Dense Bituminous Macadam (DBM) 100-120 TPH batch type HMP producing an average output of 75 tones per hour using crushed aggregates of specified grading, premixed with VG-30 bituminous binder of grade 60/70 @ 4.0 to 4.5 per cent by weight of total mix and filler by weight of total mix and transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers of 8-10 M.T. static weight including all material, labour and machinery with all leads and lifts including surveying wherever necessary etc. complete including cost of bitumen as per clause 505 of MoRT&H (Fifth Revision) specification and as per the direction of engineer-in- charge. (50mm Thick)	cum	0.00						
7	Providing and applying single tack coat of liquid bituminous material of RS (Rapid setting emulsion) over the first layer of DBM surface which is preparatory to lay another layer of DBM as a tack coat @ 0.2 kg / sqm. area and applying another layer of single tack coat over the finished layer of DBM surface which is preparatory to lay bituminous concrete as a tack coat @0.20 kg/sqm. Area, as per Table No.500-5 of MORT & H (Fifth Revision) specifications. Including cost of bitumen and cleaning the surface by mechanical means as per the direction of engineer-in-charge.	sqm	0.00						

Providing and apping Bituminous concrete with 100-120 TPH listsh type IMP producing an average output of 75 tones per hour using crushed aggregates of specified grading, premixed with V-0.09 5.5% (precentage by weight of loggregates of the start of the second start of the se				1	1		
bottom width 115 and 150 mm respectively, 300 mm high in M20 grade Plain Coment Concrete (FCC) using PPC and hard broken stone jelly of 20 mm nominal and downgraded size with 270 kg of cement and 50 kg of fly ash in replacement of cement) and hard broken stone jelly of 20 mm nominal and downgraded size with 1100 mm thick, foundation having 68 mm projection beyond kerb stone, foundation concrete laid manually, finish the surface neatly, shape and dimensions as per drawing, curing and groove cutting for expansion at regular intervals all complete as per clause 409 of MRT&H (Fifth Revision) specification and as per the direction of engineer-in-charge. 0.00 Providing and applying 2.5 mm thick including reflectorising glass beads 250 gms per sqm area, thickness of 2.5 mm is exclusive of surface applied glass beads as per RG.25.7. The road marking strips for center line and stop line (refor reflective) of specified shade/ colour using hot thermoplastic material by fully/ semi automatic thermoplastic paint applicator machine fitted with profile shoe, glass beads sqm 2000.00 0 operator on road surface including cost of material, labour, T&P, cleaning the road surface of all dirty, easel, oil; grease and foreign matter including, srgm 2000.00 11 brooming the surface free from morar drops and other foreign matter including preparing the surface free from morar drops and other foreign matter including srgm in grease with approved external Weathershield primer after thoroughly srgm in Missing of Reflective Raised Pavement marker (RPMS)/ Cat eyes / Road studs confirming to ASTM D4280 type H, having reflective panels made of prismatic ters of total internal reflections, drawings and direction of Engineer-in-charge. Nos 0.00 0.00 0.00	producing an average specified grading, pre- and lime filler @ 39 Formula, transporting finisher with sensor with smooth wheel compaction as per Cla	e output of 75 tones per hour using crushed aggregates mixed with VG-40 @ 5.5% (percentage by weight of total mi % (percentage by weight of Aggregate) filler as per Job M g the hot mix to work site, laying with a hydrostatic pav control to the required grade, level and alignment, rollin ed, vibratory and tandem rollers to achieve the desiru ause No. 507 of MORTH specification, complete in all respect	of x) lix er ng cum ed	1440.00			
per sqm_area, thickness of 2.5 mm is exclusive of surface applied glass beads as per IRG:35. The road marking strips for center line and stop line (ruro reflective) of specified shade/ coloru using hot thermoplastic material by fully/ semi automatic thermoplastic paint applicator machine fitted with profile shoe, glass beads of dispenser, propane tank heater and profile shoe heater, driven by experienced operator on road surface including cost of material, labour, T&P, cleaning the road surface of all dirt, seals, oil, grease and foreign material etc. complete as per drawings and direction of Engineer-in- charge and accordance with applicable specifications. 2000.00 Providing and applying two coats with Synthetic Enamel Paint on kerb stone after filling the surface of approved brand and shade on concrete surface including priming coat with approved external Weathershield primer after thoroughly the surface free from mortar drops and other foreign matter including preparing the surface free from mortar drops and other foreign matter including struct as per specifications, drawings and direction of Engineering-charge. sem Providing and fixing of Reflective Raised Pavement marker (RPM's)/ Cat eyes / Road studs confirming to ASTM 04280 type H, having reflective panels made of prismatic lens should be electronically fixed (welded) to the body made of polycarbonate mould, with a height of 20mm, size of 130mm X105mm and reflecting area of 133cqm with the slope of retro reflective surface within the limit of 35+ 5 degree to the base on either side. The marker shaug of zero degree and 0.2 degree observation angle shall be 112 mcd/lux with color multiphyling factor on either cases for white, yellow and red markers being 1.0, 0.6 and 0.25 respectively. The RPM's should be fixed by using two numbers of polymer shanks using appropriate adhesive as recommended and crifted by the RPM manufacturer. T	bottom width 115 ar Cement Concrete (PCC and downgraded size Cement Concrete (PCC of cement) and hard b 173 kg of cement and 100 mm thick, founda concrete laid manual drawing, curing and g per clause 409 of	nd 150 mm respectively, 300 mm high in M20 grade Pla C) using PPC and hard broken stone jelly of 20 mm nomin with 270 kg of cement and 50 kg of fly ash on M10 grade Pla C) using OPC 53 grade (considered 20% fly ash in replaceme roken stone jelly of 20 mm nominal and downgraded size wi 43 kg of fly ash tion having 68 mm projection beyond kerb stone, foundation ly, finish the surface neatly, shape and dimensions as p roove cutting for expansion at regular intervals all complete MoRT&H (Fifth Revision) specification and as per th	in hal in tt tth er as	0.00			
filling the surface of approved brand and shade on concrete surface including priming coat with approved external Weathershield primer after thoroughly brooming the surface free from mortar drops and other foreign matter including preparing the surface even and sand paper smooth, cost of materials, labour etc. complete as per specifications, drawings and direction of Engineering-charge. sqm 1848.00 Providing and fixing of Reflective Raised Pavement marker (RPM's)/ Cat eyes / Road studs confirming to ASTM D4280 type H, having reflective panels made of prismatic lens of total internal reflection, the prismatic lens should be electronically fixed (welded) to the body made of polycarbonate mould, with a height of 20mm, size of 130mm X105mm and reflecting area of 13Sqcm with the slope of retro reflective surface within the limit of 35+ 5 degree to the base on either side. The marker shape II display an initial minimum luminous intensity of 279mcd/lux at an entrance angle of zero degree and observation angle of 0.2degree. The corresponding values for 20 degree entrance and 0.2 degree observation angle shall be 112 mcd/lux with color multiplying factor on either cases for white, yellow and red markers bieng 1.0, 0.6 and 0.25 respectively"The RPM's should be fixed by using two numbers of p0.9 mer shanks using appropriate adhesive as recommended and certified by the RPM manufacturer. The raised pavement marker should support a sufficient minimum load 13635 Kg in accordance with specification and guidlines. (3M Make) Nos 30.00 13 Road Signage with 3M sheet Nos 30.00 Immuno to the fore the second sufficient minimum load 13607 Kg in accordance with specification and guidlines. (3M Make) Nos 30.00 Immuno total for Work Order	per sqm area, thicknee IRC:35 . The road ma specified shade/ color thermoplastic paint a dispenser, propane ta operator on road su road surface of all dir drawings and direct	ss of 2.5 mm is exclusive of surface applied glass beads as p rking strips for center line and stop line (retro reflective) ur using hot thermoplastic material by fully/ semi automat applicator machine fitted with profile shoe, glass bea- ank heater and profile shoe heater, driven by experience urface including cost of material, labour, T&P, cleaning th t, seals, oil, grease and foreign material etc. complete as p	er of tic ds ed sqm he er	2000.00			
studs confirming to ASTM D4280 type H, having reflective panels made of prismatic lens of total internal reflection, the prismatic lens should be electronically fixed (welded) to the body made of polycarbonate mould, with a height of 20mm, size of 130mm X105mm and reflecting area of 13Sqcm with the slope of retro reflective surface within the limit of 35+5 degree to the base on either side. The marker shape II display an initial minimum luminous intensity of 279mcd/lux at an entrance angle of zero degree and observation angle of 0.2degree. The corresponding values for 20 degree entrance and 0.2 degree observation angle shall be 112 mcd/lux with color multiplying factor on either cases for white, yellow and red markers being 1.0, 0.6 and 0.25 respectively"The RPM's should be fixed by using two numbers of polymer shanks using appropriate adhesive as recommended and certified by the RPM manufacturer. The raised pavement marker should support a sufficient minimum load 13635 Kg in accordance with specification and guidlines. (3M Make)Nos30.0013Road Signage with 3M sheetNos30.0014Safety Tape 3 M yellow ColourRmtr0.00	filling the surface of priming coat with a brooming the surface preparing the surface	approved brand and shade on concrete surface includin approved external Weathershield primer after thorough free from mortar drops and other foreign matter includin even and sand paper smooth, cost of materials, labour e	ng Ily ng sqm	1848.00			
14 Safety Tape 3 M yellow Colour Rmtr 0.00 Total for Work Order	studs confirming to A lens of total internal (welded) to the body 130mm X105mm and surface within the lim II display an initial mi of zero degree and ob degree entrance and 0 multiplying factor on and 0.25 respectively' shanks using approp manufacturer. The ra	STM D4280 type H, having reflective panels made of prismal reflection, the prismatic lens should be electronically fixe made of polycarbonate mould, with a height of 20mm, size l reflecting area of 13Sqcm with the slope of retro reflecti it of 35+ 5 degree to the base on either side. The marker sha nimum luminous intensity of 279mcd/lux at an entrance ang servation angle of 0.2degree. The corresponding values for 2 0.2 degree observation angle shall be 112 mcd/lux with col either cases for white, yellow and red markers being 1.0, 0 "The RPM's should be fixed by using two numbers of polym riate adhesive as recommended and certified by the RP ised pavement marker should support a sufficient minimu	tic ed of ye pe gle 20 or Nos 0.6 er M	0.00			
14 Safety Tape 3 M yellow Colour Rmtr 0.00 Total for Work Order	13 Road Signage with 2M	sheet	Noc	30.00			
Total for Work Order							
Grand Total	Total for Work Order						-
orana rotat	Grand Total						-
	1 Data abould be inclusi	ive of cess.all charges .labour charges except GST. GST nil agai	not I UT				

1 Rate should be inclusive of cess, all charges , labour charges except GST, GST nil against LUT.

2 Time is essence of the Contract. Work to be completed within 60 days.

Any extra Items /increase in qtys. other than BOQ shall be pre-intimated before execution. Such Items shall be recorded in Site
Instruction book and same shall be paid as per approval by Engineer-in Charge based on proper rate analysis (in case of extra items) by Contracts Deptt and the same shall be paid in final invoice.